

# PRODUCT DATASHEET

## DP HOUSING 600 2x Lamp IP65

DAMP PROOF HOUSING GEN 2 | Damp-proof luminaire for T8 LED lamps

---

### Areas of application

- Parking lots, warehouses, production areas



---

### Product benefits

- Prewired for easy installation of tubular AC LED lamps
- Robust housing
- Easy and quick installation
- 5 years guarantee

---

### Product features

- Luminaire housing, available for 1 or 2 T8 LED lamps
- Type of protection: IP65
- Suitable for SubstiTUBE EM/UN and SubstiTUBE Connected



TECHNICAL DATA

Electrical data


Nominal voltage	220...240 V
Mains frequency	50...60 Hz
Protection class	I

Photometrical data

Luminous intensity	-
Flickering metric (Pst LM)	-
Stroboscope effect metric (SVM)	-
Beam angle	105 °

Dimensions & Weight

Length	651.00 mm
Width	103.00 mm
Height	75.00 mm
Product weight	850.00 g



Materials & Colors

Product color	Grey
Housing color	Gray
Body material	Polycarbonate (PC)
Cover material	Polycarbonate (PC)
Light emitting surface material	Polycarbonate (PC)
Glow Wire Test according to IEC 60695-2-12	650 °C
Mercury content	0.0 mg

Application & Mounting

Ambient temperature range	-30...+40 °C
---------------------------	--------------

Temperature range at storage	-20...80 °C
Type of connection	Screw terminal
Type of protection	IP65
Protection class IK (shock resistance)	IK08
Dimmable	No
Mounting type	Surface
Mounting location	Ceiling
Application environment	Indoor
With light source	No

Certificates & Standards

Standards	CE / TÜV Rheinland / EAC / ROHS / UKCA
Luminaire with limited surface temperature, "D sign"	No
Ball shot safe	No






Additional product data


Number of illuminants	-
-----------------------	---

EQUIPMENT / ACCESSORIES

– All required accessories included

DOWNLOAD DATA

Documents and certificates		Document name
	User Instruction	UI_DampProof_Housing_incl-TH-KIT
	Legal information	Legal Insert DP Housing IP65
	Declarations of conformity	DAMP PROOF 600 2XLAMP HOUSING IP65
	Declarations Of Conformity UKCA	DAMP PROOF 600 IP65
	Declarations Of Conformity UKCA	DAMP PROOF 600 LAMP HOUSING

Tender texts		Document name
	Tender documents	DAMP PROOF HOUSING 600 2x Lamp IP65-EN

LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4058075312418	Folding box 1	77 mm x 110 mm x 660 mm	1006.00 g	5.59 dm³
4058075312425	Shipping box 6	670 mm x 231 mm x 245 mm	6794.00 g	37.92 dm³

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

References / Links

– For Guarantee see [www.ledvance.com/guarantee](http://www.ledvance.com/guarantee)

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.