

OSRAM



Electric Automation
Automation specialists

Referência: HALOPAR 16 40 W 230 V 35°
E14

Código: 4050300938479

HAL HALOPAR 16 (Até final de estoque)
64822 FL 40W E14 230V

A partir de Electric Automation Network



HALOPAR 16 40 W 230 V 35° E14

Electrical data

Nominal wattage	40.00 W
Nominal voltage	230 V
Rated wattage	40.00 W
Power factor λ	1.00

Photometrical data

Nominal useful fluxo luminous 90°	250 lm
Luminous intensity	650 cd
Rated cor temperature	2800 K
Light cor (designation)	Warm White
Color rendering index Ra	100
Lúmen main.fact.at end of nom.life time	0.75
Rated useful fluxo luminous 90°	250 lm
Rated peak intensity	820 cd

Light technical data

Beam angle	35 °
------------	------

Nominal beam angle	35 °
Starting time	0.0 s
Warm-up time (60 %)	0.00 a
Rated beam angle (half peak value)	35.00 °

Dimensions & weight

Diameter	50.7 mm
Overall length	73.0 mm
Length	75.0 mm
Outer bulb	PAR51
Maximum diameter	51.0 mm

Lifespan

Nominal lamp life time	2000 h
Rated lamp life time	2000 h
Number of switching cycles	50000

Atd>

Base (standard designation)	E14
Mercury content	0.0 mg
Mercury-free	Yes
Product remark	Not suitable for outdoor use or damp conditions/Banned from 1.9.2016 as per EU phase-out plano

Capabilities

Burning position	Any
Dimmable	Yes

Certificates & standards

Energy efficiency class	D
Energy consumption	40 kWh/1000h

Country specific categorizations

ILCOS	Furnace fun/UB-40-230-E14-51/35
-------	---------------------------------