

Produktdatablad

P DIM PAR16 8 W/840 GU10

PARATHOM DIM PAR 16 | Dimbara LED-reflektorlampor PAR16 med stiftsockel



Tekniska data

Elektriska data

ZLDV_Rated wattage [AGGR]	8.00 W
ZLDV_Nominal wattage [AGGR]	8.00 W
ZLDV_Nominal voltage [AGGR]	220...240 V
ZLDV_Claimed equiv. conventional lamp power [AGGR]	80 W
ZLDV_Operating frequency [AGGR]	50...60 Hz
ZLDV_Nominal current [AGGR]	0.047 A


Fotometrisk data

ZLDV_Nominal luminous flux [AGGR]	575 lm
ZLDV_Rated luminous flux [AGGR]	575 lm
ZLDV_Rated color temperature [AGGR]	4000 K
ZLDV_Color rendering index Ra [AGGR]	≥80
ZLDV_Light color (designation) [AGGR]	Cool White
ZLDV_Standard deviation of color matching [AGGR]	≤5 sdcn
ZLDV_Nominal useful luminous flux 90° [AGGR]	575 lm
ZLDV_Rated useful luminous flux 90° [AGGR]	575 lm
ZLDV_Rated peak intensity [AGGR]	1439 cd
ZLDV_Color temperature [AGGR]	4000 K
ZLDV_Luminous flux [AGGR]	575 lm
ZLDV_Lumen main.fact.at end of nom.life time [AGGR]	0.70

Ljustekniska värden

ZLDV_Beam angle [AGGR]	36 °
ZLDV_Nominal beam angle [AGGR]	36 °
ZLDV_Rated beam angle (half peak value) [AGGR]	36.00 °
ZLDV_Starting time [AGGR]	< 0.5 s

Mått



ZLDV_Overall length [AGGR]	55.0 mm
ZLDV_Diameter [AGGR]	51.0 mm
ZLDV_Outer bulb [AGGR]	PAR51
ZLDV_Product weight [AGGR]	56.00 g
ZLDV_Length [AGGR]	55.0 mm
ZLDV_Maximum diameter [AGGR]	51.0 mm

Temperaturer och driftsförhållanden

ZLDV_Ambient temperature range [AGGR]	-20...+40 °C
---------------------------------------	--------------

Livslängder

ZLDV_Nominal lamp life time [AGGR]	25000 h
ZLDV_Rated lamp life time LEDr [AGGR]	25000 h
ZLDV_Number of switching cycles [AGGR]	100000
ZLDV_Lumen maintenance at end of service life [AGGR]	0.70

Tillägg produktdata

ZLDV_Base (standard designation) [AGGR]	GU10
ZLDV_Mercury content [AGGR]	0.0 mg
ZLDV_Mercury-free [AGGR]	Yes
Bortskaffande enl. WEEE-direktivet	Ja
Produkten ersätts av EAN	4058075449244
ZLDV_Product remark [AGGR]	All technical parameters apply to the entire lamp/Due to the complex production process for light-emitting diodes, the typical values shown for the technical LED parameters are purely statistical values that do not necessarily match the actual technical parameters of each individual product, which can vary from the typical value

Produktdatablad

Produkten ersätts av EAN	4052899958029
--------------------------	---------------

Användningsområden

ZLDV_Dimmable [AGGR]	Yes
----------------------	-----

Certifikat och Standarder

ZLDV_Energy efficiency class [AGGR]	A+
ZLDV_Energy consumption [AGGR]	8 kWh/1000h
ZLDV_Type of protection [AGGR]	IP20

Landspecifika kategorier

ZLDV_Order reference [AGGR]	LPPAR16D8036 8W
-----------------------------	-----------------

Environmental information

Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACH)	
Date of Declaration	18-04-2022
Primary Article Identifier	4058075095441
Declaration No. in SCIP database	In work

Ecodesign regulation information:

Separate control gear and light sources must be disposed of at certified disposal companies in accordance with Directive 2012/19/EU (WEEE) in the EU and with Waste Electrical and Electronic Equipment (WEEE) Regulations 2013 in the UK. For this purpose, collection points for recycling centres and take-back systems (CRSO) are available from retailers or private disposal companies, which accept separate control gear and light sources free of charge. In this way, raw materials are conserved and materials are recycled.

Referenser / Länkar

För dimmer kompatibilitet se

▶ www.osram.com/DIM

For further products and actual information concerning LED lamps see

▶ www.osram.se/ledlampor

For Guarantee see

▶ www.osram.se/garanti

Friskrivningsklausul

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.

OSRAM is distribution partner
of LEDVANCE of LAMPS

OSRAM

OSRAM GmbH
Marcel-Breuer-Strasse 6
80807 Munich, Germany