

PRELIMINARY - PRODUCT DATASHEET

FLOODLIGHT LUX 20W 830 BLACK

FLOODLIGHT LUX | Floodlight luminaire with milky glass



Areas of application

- Gardens and other outdoor areas
- Workshops, garages, covered outdoor storage areas
- Outdoor use (IP65)

Product benefits

- Durable product due to 3 years warranty and 30,000 h lifetime
- Milky glass reducing the glare effect
- Bent-over bracket for easy mounting

Product features

- Modern design
- Lifetime up to 30,000 h
- 3 years warranty
- Available with color temperature: 3,000 K, 4,000 K, 6,000 K
- Frosted diffuser



TECHNICAL DATA

Electrical data


Nominal wattage	20.00 W
Nominal voltage	220...240 V
Mains frequency	50 Hz
Nominal current	91.000 mA
Max. number of luminaires per miniature circuit breaker B16	145
Max. number of luminaires per miniature circuit breaker C16	145
Power factor λ	> 0.90
Total harmonic distortion	< 20 %
Protection class	I
Operating mode	Integrated LED driver

Photometrical data

Luminous flux	1800 lm
Luminous efficacy	90 lm/W
Color temperature	3000 K
Light color (designation)	Warm White
Color rendering index Ra	80
Standard deviation of color matching	6 sdcn
Photobiological safety group acc. to EN62778	RG1
Beam angle	105 °

Dimensions & Weight

Length	124.00 mm
Width	99.00 mm
Height	30.00 mm
Product weight	212.00 g



FL 20W

Materials & Colors

Product color	Black
Housing color	Black
Body material	Aluminum
Glow Wire Test according to IEC 60695-2-12	650 °C
Mercury content	0.0 mg

Application & Mounting

Ambient temperature range	-20...+40 °C
Temperature range at storage	-30...+80 °C
Type of connection	Cable, 3-pole
Type of protection	IP65
Protection class IK (shock resistance)	IK06
Dimmable	No
Mounting type	Surface
Mounting location	Wall
With light source	Yes

Lifespan

Number of switching cycles	20000
----------------------------	-------

Certificates & Standards

Standards	CE / EAC / UKCA
Luminaire with limited surface temperature, "D sign"	No
Replaceable light source (EPREL)	Not replaceable

EQUIPMENT / ACCESSORIES

– All required accessories included

DOWNLOAD DATA

Documents and certificates		Document name
	User instruction / safety instructions	FL LUX IP65 BK
	Addon technical information	FL LUX/SENSOR IP65 BK
	Legal information	Informationstext 18 Abs 4 ElektroG
	Legal information	FL LUX/SENSOR IP65 BK
	Declarations of conformity UKCA	FL VITAL/ EFFECT/ FLUX IP65 BK

LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4099854489488	Folding box 1			
4099854489495	Shipping box 10	285 mm x 200 mm x 138 mm	2525.00 g	7.87 dm ³

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.