

# PRODUCT DATASHEET

## FLOODLIGHT LED 50 W 4000 K BK

LEDVANCE FLOODLIGHT LED | LED floodlight luminaires



### Areas of application

- Replacement for floodlights with halogen lamps
- Car parks and underpasses
- Garages
- Public areas
- Building facades
- Construction areas

### Product benefits

- Energy savings of up to 90 % compared to halogen lamp floodlights
- Optimized weight and size due to compact design
- Very homogenous light

### Product features

- Luminaire efficacy: up to 100 lm/W
- Beam angle: 100°
- Type of protection: IP65



TECHNICAL DATA


Electrical data

Nominal wattage	50.00 W
Nominal voltage	220...240 V
Mains frequency	50...60 Hz
Nominal current	630.000 mA
Power factor $\lambda$	> 0.90
Protection class	I
Operating mode	Electronic control gear (ECG)


Photometrical data

Luminous flux	5000 lm
Luminous efficacy	100 lm/W
Color temperature	4000 K
Light color (designation)	Cool White
Color rendering index Ra	$\geq 80$
Standard deviation of color matching	$\leq 5$ sdcn
Photobiological safety group acc. to EN62778	RG0
Beam angle	100 °






LDC typ cone



LDC typ polar

Dimensions & Weight

Length	187.00 mm
Width	216.00 mm
Height	62.00 mm
Product weight	1270.00 g
Cable length	1000 mm



Materials & Colors

Product color	Black
Housing color	Black
Body material	Polycarbonate (PC)
Light emitting surface material	Glass
Mercury content	0.0 mg

Application & Mounting

Ambient temperature range	-20...+50 °C
Type of connection	Cable, 3-pole
Type of protection	IP65
Protection class IK (shock resistance)	IK07
Dimmable	No
Mounting type	Surface
Mounting location	Wall / Floor
Application environment	Outdoor
LED module replaceable	Not replaceable





Lifespan

Lifespan L70/B50 at 25 °C	50000 h
Lifespan L80/B10 at 25 °C	30000 h
Lifespan L90/B10 at 25 °C	15000 h
Number of switching cycles	30000


Certificates & Standards

Standards	CE / CB / TÜV SÜD / EAC / RoHS
-----------	--------------------------------

DOWNLOAD DATA

DOWNLOAD DATA	
	Declarations Of Conformity CE
	On-Pack-Info
	IES file (IES)
	LDT file (Eulumdat)



DOWNLOAD DATA	
	UGR file (UGR table)

LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4058075810990	Folding box 1	65 mm x 234 mm x 217 mm	1.34 g	3.30 dm <sup>3</sup>
4058075811003	Shipping box 10	482 mm x 348 mm x 232 mm	14.21 g	38.91 dm <sup>3</sup>

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.

