

# PRODUCT DATASHEET

## ECO CLASS DAMP PROOF 600 21 W 6500 K IP65 TH

ECO CLASS DAMP PROOF GEN 2 | Damp-proof luminaires, classic shape

---

### Areas of application

- Industrial and storage facilities
- Car parks and underpasses
- Garages
- Workshops, assembly lines



---

### Product benefits

- Evenly distributed light
- Energy savings of up to 50 % (compared to luminaires that use fluorescent lamps)
- Easy installation, no tools required for connection

---

### Product features

- High luminous efficacy: up to 120 lm/W
- Type of protection: IP65
- Beam angle: 120°
- Through-wired (L, N, E)
- Polycarbonate housing



---

**TECHNICAL DATA****Electrical data**

Nominal wattage	21.00 W
Nominal voltage	220...240 V
Mains frequency	50...60 Hz
Inrush current	12 A
Inrush current time $T_{h50}$	100 $\mu$ s
Max. number of luminaires per miniature circuit breaker B16	62
Max. number of luminaires per miniature circuit breaker C10	50
Max. number of luminaires per miniature circuit breaker C16	80
Power factor $\lambda$	$\geq 0.90$
Total harmonic distortion	20 %
Protection class	II
Operating mode	Integrated LED driver

**Photometrical data**


Luminous flux	2520 lm
Luminous efficacy	120 lm/W
Color temperature	6500 K
Light color (designation)	Cool Daylight
Color rendering index Ra	> 80
Standard deviation of color matching	< 5 sdcm
Luminous intensity	-
Flickering metric (Pst LM)	-
Stroboscope effect metric (SVM)	-
Photobiological safety group acc. to EN62778	RG1
Photobiological safety group acc. to EN62471	RG1
Beam angle	120 °

ECO CLASS DAMP PROOF 21W

ECO CLASS DAMP PROOF

Dimensions & Weight

Length	610.00 mm
Width	70.50 mm
Height	70.40 mm
Product weight	690.00 g



Materials & Colors

Product color	Gray
Housing color	Gray
Body material	Polycarbonate (PC)
Cover material	Polycarbonate (PC)
Light emitting surface material	Polycarbonate (PC)
Glow Wire Test according to IEC 60695-2-12	650 °C
Mercury content	0.0 mg

Application & Mounting

Ambient temperature range	-20...+40 °C
Temperature range at storage	-40...+70 °C
Type of connection	Screwless
Type of protection	IP65
Protection class IK (shock resistance)	IK08
Dimmable	No
Mounting type	Surface
Mounting location	Ceiling / Wall
Application environment	Indoor
LED module replaceable	Not replaceable
With light source	Yes

Lifespan

Lifespan L70/B50 at 25 °C	30000 h <sup>1)</sup>
Number of switching cycles	100000

<sup>1)</sup> t[h]: L70 / B50 @ 25 °C (Ta), t[h]: L80 / B10 @ 25 °C (Ta), t[h]: L90 / B10 @ 25 °C (Ta)

Certificates & Standards

Standards	CE / EAC / RoHS / REACH
-----------	-------------------------

Luminaire with limited surface temperature, "D sign"	Yes
--	-----



### Additional product data





Number of illuminants	-
-----------------------	---

### EQUIPMENT / ACCESSORIES

– Mounting material for wall and ceiling installations included

### DOWNLOAD DATA

Documents and certificates	Document name
 User instruction	User Instruction ECO CLASS DAMPPROOF
 Declarations Of Conformity CE	CE Declaration of Conformity ECO CLASS DAMP PROOF

Photometric and lighting design files	Document name
 LDT file (Eulumdat)	ECO CLASS DAMP PROOF 600 TH 21W 6500K IP65
 UGR file (UGR table)	ECO CLASS DAMP PROOF 21W
 LDC typ cone	ECO CLASS DAMP PROOF 21W
 LDC typ polar	ECO CLASS DAMP PROOF

### LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4058075463844	Folding box 1	636 mm x 77 mm x 75 mm	823.00 g	3.67 dm <sup>3</sup>
4058075463851	Shipping box 9	655 mm x 250 mm x 250 mm	8363.00 g	40.94 dm <sup>3</sup>

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

### References / Links

– For Guarantee see [www.ledvance.com/guarantee](http://www.ledvance.com/guarantee)

### DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.