

# PRODUCT DATASHEET

## FL PFM 20 W 6500 K SYM 100 BK

FLOODLIGHT 20 W | Versatile floodlight with up to 2400 lm light output



### Areas of application

- Replacement for floodlights with halogen lamps
- Outdoor use (IP65)
- Public areas
- Building facades
- Construction areas
- Gardens, balconies and other outdoor areas

### Product benefits

- Bright, robust and durable
- Safe and very uniform illumination, due to frosted and tempered glass diffuser
- No upper light output ratio (ULOR 0%) when mounted at 0° tilt
- Energy savings of up to 90 % compared to halogen lamp floodlights
- 5 years guarantee

### Product features

- Reflector-based, symmetric light distribution with 100° x 100° beam angle
- Integrated wide voltage driver, suitable for 100 - 277 V<sub>AC</sub>
- Surge protection: up to 4 kV (L/N-PE), 2 kV (L-N)
- Mounting bracket with 30° angle and wide rotation area
- Pre-installed, flexible 1 m cable (H05RN-F), wrapped 3 x 1.0 mm<sup>2</sup> single wires




---

**TECHNICAL DATA****Electrical data**


|                                                             |                       |
|-------------------------------------------------------------|-----------------------|
| Nominal wattage                                             | 20.00 W               |
| Nominal voltage                                             | 100...277 V           |
| Mains frequency                                             | 50...60 Hz            |
| Nominal current                                             | 98 mA                 |
| Inrush current                                              | 5.68 A                |
| Inrush current time $T_{h50}$                               | 35 $\mu$ s            |
| Max. number of luminaires per miniature circuit breaker B16 | 93                    |
| Max. number of luminaires per miniature circuit breaker C10 | 67                    |
| Max. number of luminaires per miniature circuit breaker C16 | 108                   |
| Power factor $\lambda$                                      | > 0.90                |
| Total harmonic distortion                                   | < 20 %                |
| Protection class                                            | I                     |
| Operating mode                                              | Integrated LED driver |

**Photometrical data**

|                                              |                           |
|----------------------------------------------|---------------------------|
| Luminous flux                                | 2400 lm                   |
| Luminous efficacy                            | 120 lm/W                  |
| Color temperature                            | 6500 K                    |
| Light color (designation)                    | Cool Daylight             |
| Color rendering index Ra                     | $\geq 80$                 |
| Standard deviation of color matching         | $\leq 5$ sdc <sub>m</sub> |
| Luminous intensity                           | -                         |
| Flickering metric (Pst LM)                   | -                         |
| Stroboscope effect metric (SVM)              | -                         |
| Photobiological safety group acc. to EN62778 | RG1                       |
| Photobiological safety group acc. to EN62471 | RG1                       |
| Beam angle                                   | 100 ° x 100 °             |





FL PFM 20W6500K SYM 100 BK



FL PFM 20W6500K SYM 100 BK

Dimensions & Weight

|                |           |
|----------------|-----------|
| Length         | 144.00 mm |
| Width          | 156.00 mm |
| Height         | 42.00 mm  |
| Product weight | 520.00 g  |
| Cable length   | 1000 mm   |



## Materials & Colors

|                                            |          |
|--------------------------------------------|----------|
| Product color                              | Black    |
| Housing color                              | Black    |
| Body material                              | Aluminum |
| Light emitting surface material            | Glass    |
| Glow Wire Test according to IEC 60695-2-12 | 650 °C   |

## Application & Mounting

|                                        |                        |
|----------------------------------------|------------------------|
| Ambient temperature range              | -30...+50 °C           |
| Temperature range at storage           | -40...+70 °C           |
| Type of connection                     | Cable, 3-pole          |
| Type of protection                     | IP65                   |
| Protection class IK (shock resistance) | IK07                   |
| Dimmable                               | No                     |
| Mounting type                          | Surface                |
| Mounting location                      | Wall / Ceiling / Floor |
| Application environment                | Outdoor                |
| Adjustable                             | Yes                    |
| LED module replaceable                 | Not replaceable        |
| With light source                      | Yes                    |

## Lifespan

|                            |                       |
|----------------------------|-----------------------|
| Lifespan L70/B50 at 25 °C  | 70000 h <sup>1)</sup> |
| Lifespan L80/B10 at 25 °C  | 55000 h <sup>1)</sup> |
| Lifespan L90/B10 at 25 °C  | 35000 h               |
| Number of switching cycles | 100000                |

<sup>1)</sup> t[h]: L70 / B50 @ 25 °C (Ta), t[h]: L80 / B10 @ 25 °C (Ta), t[h]: L90 / B10 @ 25 °C (Ta)

## Control gear

|                             |        |
|-----------------------------|--------|
| Output current              | 230 mA |
| ECG - Output ripple current | < 50 % |

## Certificates & Standards

|           |                                   |
|-----------|-----------------------------------|
| Standards | CE / CB / ENEC / EAC / RoHS / EPD |
|-----------|-----------------------------------|

|                                                      |                      |
|------------------------------------------------------|----------------------|
| Luminaire with limited surface temperature, "D sign" | No                   |
| Ball shot safe                                       | No                   |
| EPD                                                  | LEDV-00009-V01.01-EN |

DOWNLOAD DATA

| Documents and certificates                                                          |                                 | Document name               |
|-------------------------------------------------------------------------------------|---------------------------------|-----------------------------|
|    | User instruction                | FL PFM SYM                  |
|    | Addon Technical Information     | FL PFM SYM                  |
|    | Addon Technical Information     | LSI FL PFM SYM              |
|    | Packaging insert                | FL PFM SYM                  |
|    | Declarations Of Conformity CE   | FL PFM                      |
|   | Declarations Of Conformity UKCA | FL PFM SYM                  |
|  | Declarations Of Conformity UKCA | FL PFM                      |
| Photometric and lighting design files                                               |                                 | Document name               |
|  | IES file (IES)                  | FL PFM 20W6500K SYM 100 BK  |
|  | LDT file (Eulumdat)             | FL PFM 20W6500K SYM 100 BK  |
|  | ULD file (DIALux)               | FL PFM 20W-6500K SYM 100 BK |
|  | ROLF file (RELUX)               | FL PFM 20W-6500K SYM        |
|  | UGR file (UGR table)            | FL PFM 20W6500K SYM 100 BK  |
|  | LDC typ cone                    | FL PFM 20W6500K SYM 100 BK  |
|  | LDC typ polar                   | FL PFM 20W6500K SYM 100 BK  |




| CAD/BIM files                                                                    |                  | Document name                        |
|----------------------------------------------------------------------------------|------------------|--------------------------------------|
|  | BIM_Revit_3D     | Floodlight G3                        |
|  | CAD_STEP_3D      | FL G3 20W                            |
| Tender texts                                                                     |                  | Document name                        |
|  | Tender documents | FLOODLIGHT 20 W 6500 K SYM 100 BK-EN |

## LOGISTICAL DATA

| Product code  | Packaging unit (Pieces/Unit) | Dimensions (length x width x height) | Gross weight | Volume                |
|---------------|------------------------------|--------------------------------------|--------------|-----------------------|
| 4058075421059 | Folding box<br>1             | 161 mm x 62 mm x 135 mm              | 572.00 g     | 1.35 dm <sup>3</sup>  |
| 4058075421066 | Shipping box<br>12           | 396 mm x 336 mm x 161 mm             | 7510.00 g    | 21.42 dm <sup>3</sup> |

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

## ADDITIONAL CATALOG INFORMATION



## References / Links

– For Guarantee see [www.ledvance.com/guarantee](http://www.ledvance.com/guarantee)

## DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.