


# PRODUCT DATASHEET

## LED FACADE UPDOWN 12 W 3000 K GY

**LEDVANCE OUTDOOR LED FACADE UPDOWN | Luminaires with classic shape and light outlet up and down**



---

### AREAS OF APPLICATION

- Outdoor
- Building facades
- Decorative illumination

---

### PRODUCT BENEFITS

- Energy-efficient thanks to LED technology
- 5 years guarantee
- Easy and quick installation
- Homogeneous light output

---

### PRODUCT FEATURES

- Very bright and functional outdoor LED luminaires
- Type of protection: IP54
- Die-cast aluminum housing
- Available in two housing colors: white and dark gray
- Diffuser made of clear glass



TECHNICAL DATA

Electrical data

|                 |               |
|-----------------|---------------|
| Operating mode  | Mains voltage |
| Mains frequency | 50/60 Hz      |
| Power factor λ  | >0.5          |
| Nominal wattage | 12.00 W       |
| Nominal voltage | 220...240 V   |
| Nominal current | 0.055 A       |


Photometrical data

|                                      |            |
|--------------------------------------|------------|
| Luminous efficacy                    | 60 lm/W    |
| Luminous flux                        | 700 lm     |
| Color temperature                    | 3000 K     |
| Light color (designation)            | Warm White |
| Color rendering index Ra             | ≥80        |
| Standard deviation of color matching | <6 sdcm    |

Light technical data

|            |          |
|------------|----------|
| Beam angle | 280.00 ° |
|------------|----------|

Dimensions & weight



|                |          |
|----------------|----------|
| Length         | 55.0 mm  |
| Width          | 90.0 mm  |
| Height         | 160.0 mm |
| Product weight | 480.00 g |

Colors & materials

|               |      |
|---------------|------|
| Housing color | Gray |
| Product color | Gray |

|                       |          |
|-----------------------|----------|
| <b>Body material</b>  | Aluminum |
| <b>Cover material</b> | Glass    |

### Temperatures & operating conditions

|                                       |             |
|---------------------------------------|-------------|
| <b>Temperature range in operation</b> | -20...40 °C |
| <b>Ambient temperature range</b>      | -20...40 °C |

### Lifespan

|                                   |         |
|-----------------------------------|---------|
| <b>Number of switching cycles</b> | 15000   |
| <b>Lifespan L70 at 25 °C</b>      | 30000 h |

### Additional product data

|                          |                              |
|--------------------------|------------------------------|
| <b>Mounting location</b> | Wall                         |
| <b>Product remark</b>    | Available from February 2018 |

### Capabilities

|                               |                             |
|-------------------------------|-----------------------------|
| <b>Type of connection</b>     | Terminal, 3-Pole (L, N, PE) |
| <b>Dimmable</b>               | No                          |
| <b>LED module replaceable</b> | Not replaceable             |

### Certificates & standards

|                                               |      |
|-----------------------------------------------|------|
| <b>Type of protection</b>                     | IP54 |
| <b>Protection class</b>                       | I    |
| <b>Protection class IK (shock resistance)</b> | IK06 |
| <b>Photobiological safety group</b>           | RG 0 |
| <b>Standards</b>                              | CE   |

## EQUIPMENT / ACCESSORIES

- Complete mounting and connecting accessories included

## LOGISTICAL DATA

| Product code  | Product description                    | Packaging unit<br>(Pieces/Unit) | Dimensions (length x<br>width x height) | Volume                | Gross weight |
|---------------|----------------------------------------|---------------------------------|-----------------------------------------|-----------------------|--------------|
| 4058075075054 | LED FACADE<br>UPDOWN 12 W 3000<br>K GY | Shipping carton box<br>6        | 245 mm x 240 mm x<br>195 mm             | 11.47 dm <sup>3</sup> | 3193.00 g    |

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

## REFERENCES / LINKS

For Guarantee see

▶ [www.ledvance.com/guarantee](http://www.ledvance.com/guarantee)

---

## DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.